

UV INK

Flexible inks with high adhesion

U V
L E D
I N K S



PAPPIJET
INKS FOR DIGITAL TEXTILE AND UV PRINTING

LED R301

Shades	Cyan, Magenta, Yellow, Black, White
Features	Flexible type No VOCs, good adhesion & flexibility, excellent color, good rubbing resistance, excellent stability
Specification	Ricoh, Toshiba, Konica Minolta, Seiko Viscosity(25°C, cP) : 19~22, surface tension (mN/m) : 20~40
Application(Substrate)	ABS, PC, PS, PET, PVC, Leather (PU), PMA, PMMA etc
Storage Condition/Packing	1kg Bottle, It is recommended to keep cool and protect from light and heat (Temperature 10~30°C)
Adhesion Chart	○○○○○○ (ABS, PC, PS, PET, PVC, PU, PMA / PMMA)

LED R312

Shades	Cyan, Magenta, Yellow, Black, White
Features	Universal type No VOCs, good adhesion & flexibility, excellent color, excellent stability and reproducibility
Specification	Ricoh, Toshiba, Konica Minolta, Seiko Viscosity(25°C, cP) : 19~22, surface tension (mN/m) : 20~40
Application(Substrate)	ABS, PET, PVC, PC, PS etc
Storage Condition/Packing	1kg Bottle, It is recommended to keep cool and protect from light and heat (Temperature 10~30°C)
Adhesion Chart	○○○○○○ (ABS, PC, PS, PET, PVC)

LED R421

Shades	Cyan, Magenta, Yellow, Black, White, Light Cyan, Light Magenta
Features	Rigid Type No VOCs, NVC Free, Excellent Hardness(up to 4H), Good Adhesion, Excellent Color Good rubbing resistance, Excellent Stability
Specification	Ricoh, Toshiba, Konica Minolta Seiko Viscosity(25°C, cP) : 19~23 cP, Surface tension : 20~40 mN/m
Application(Substrate)	ABS, PET, PVC, PC, PS etc
Storage Condition/Packing	1kg Bottle, It is recommended to keep cool and protect from light and heat (Temperature 10~30°C)
Adhesion Chart	○○○○○○ (ABS, PET, PVC, PC, PS)
Hardness Chart	○○○○○○ (PET, PMMA)

LED E312

Shades	Cyan, Magenta, Yellow, Black, White, Light Cyan, Light Magenta
Features	Universal type No VOCs, good adhesion & flexibility, excellent color, excellent stability and reproducibility
Specification	Ricoh (Mimaki), Epson Viscosity(25°C, cP) : 8~12, surface tension (mN/m) : 20~40
Application(Substrate)	ABS, PET, PVC, PC, PS etc
Storage Condition/Packing	1kg Bottle, It is recommended to keep cool and protect from light and heat (Temperature 10~30°C)
Adhesion Chart	○○○○○○ (ABS, PET, PVC, PC, PS)

**PAPIJET UV inks comply with RoHS
hazardous chemicals requirements**



Certified
ISO 9001
ISO 14001
ISO 45001



HEAD OFFICE

Kyung-In Synthetic Corporation,
572 Gonghang-daero, Yangcheon-gu,
Seoul, Republic of Korea

Tel:+82-2-3665-4001
URL:www.kisco.co

Edition 2024 Copyright ©
2024 Kyung-in Synthetic Corporation.
All rights reserved.

